

# Honeywell Power Products



POWER TO RUN YOUR SYSTEM

## Product Guide

**Honeywell**

# Introduction

Honeywell (NYSE: HON) is dedicated to providing power supplies and related accessories for the Fire, Video, Access Control and Security marketplace. Honeywell Power Products is a division of Honeywell Life Safety, a global leader in the design and manufacture of more than 40 product families, including fire alarm systems, sensors and devices, home medical care and personal protective equipment. As part of the Fire Systems Group, Honeywell Power Products is headquartered in Northford, Connecticut, operating out of a 302,000 square-foot, state-of-the-art facility supported by more than 600 employees.

Honeywell Power Products delivers high quality power solutions, from small plug-in security transformers to large fire systems

power supplies. Our company is committed to the ongoing development of cutting-edge technology, designed to provide our customers with total solutions for their power supply needs through:

• **Web Support:** Our easy to navigate web site, [www.honeywellpower.com](http://www.honeywellpower.com) contains all of the information you need to know organized by product family and model number.

• **Warranty Protection:** Our power supplies are backed by a comprehensive, lifetime warranty.

• **Application Support:** We have a comprehensive knowledge of the industry and know what products work best in your system.

• **Reliable Technical Support:** Through our toll-free technical support line, customers get immediate help with troubleshooting and solutions from industry leading product experts.

Honeywell Power Products distributes its products in North American through a network of independent dealers and distribution centers. We believe in employing talented, dedicated people, all driven by the same overriding goal - to provide our customers with sales and service support, which is second to none.

## HOW TO CONTACT US

### Honeywell Power Products

12 Clintonville Road  
Northford, CT 06472

Main Number: 203-484-7161

E-Mail: [powerproducts@honeywell.com](mailto:powerproducts@honeywell.com)

[www.honeywellpower.com](http://www.honeywellpower.com)

### Customer Service:

Phone: 1-800-627-3473

Fax: 203-484-7118

### Technical Support:

Phone: 1-800-627-3473

E-Mail: [hpp.techserv@honeywell.com](mailto:hpp.techserv@honeywell.com)

### Sales Support:

Go to [www.honeywellpower.com](http://www.honeywellpower.com) and click on "Contact Us" to locate your local sales representative.

**For the latest information:**  
[www.honeywellpower.com](http://www.honeywellpower.com)

# General Security Supplies



General purpose power supplies are used in a wide variety of applications where additional power in a compact size is needed. Typical uses are in CCTV, Security, and Access Control systems that require power for magnetic locks, heaters, blowers, cameras and other equipment combinations. These all are switch-selectable 6/12/24 VDC, with filtered and electronically regulated output. They have built-in

chargers for sealed lead acid or gel type batteries with automatic switchover to standby battery when AC power fails. Their AC input and DC output LED indicators speed wiring diagnostics. They have circuit breaker battery protection. They include battery leads and mount with foam backed tape or optional snap track HST34.

Part No.	Output Voltage	Amps	No. of Outputs	Enclosure	Dimensions (W x H x D)	Weight
<b>HPL624</b>	6/12/24VDC	1.2/1.2/.75	1	Board Only	3.5" x 3" x 1.5"	0.3
<b>HPL624-12C</b>	6/12/24VDC	1.2/1.2/.75	1	Yes	11.5" x 10" x 4.9"	12.2
<b>HPS3</b>	6/12/24VDC	2.5	1	Board Only	3.5" x 3" x 2"	0.4
<b>HPS5</b>	6/12/24VDC	4	1	Board Only	3.5" x 3" x 2"	0.6
<b>HP1224ACDC</b>	6/12/24DC and 24VAC	4A DC and 4A AC	16	Yes	15" x 14.5" x 2.75"	20
<b>HPS3PM</b>	12/24VDC	3	1	Board Only	5" x 3" x 2"	1.0
<b>HPS3PMTX</b>	12/24VDC	3	1	Yes	15" x 14.5" x 2.75"	15
<b>HPS3PMPD4</b>	12/24VDC	3	4	Yes	15" x 14.5" x 2.75"	16.7
<b>HPS3PMPD4CB</b>	12/24VDC	3	4	Yes	15" x 14.5" x 2.75"	16.7
<b>HPS3PMPD8</b>	12/24VDC	3	8	Yes	15" x 14.5" x 2.75"	17
<b>HPS3PMPD8CB</b>	12/24VDC	3	8	Yes	15" x 14.5" x 2.75"	17
<b>HPS5PM</b>	12/24VDC	4	1	Board Only	5" x 3" x 2"	1.2
<b>HPS5PMTX</b>	12/24VDC	4	1	Yes	15" x 14.5" x 2.75"	18
<b>HPS5PMPD8</b>	12/24VDC	4	8	Yes	15" x 14.5" x 2.75"	19.4
<b>HPS5PMPD8CB</b>	12/24VDC	4	8	Yes	15" x 14.5" x 2.75"	19.4
<b>HPS5PMPD16</b>	12/24VDC	4	16	Yes	15" x 14.5" x 2.75"	19.8
<b>HPS5PMPD16CB</b>	12/24VDC	4	16	Yes	15" x 14.5" x 2.75"	19.8



# AC Video Power Distribution Units



Our AC CCTV power distribution units provide a constant source of 24VAC to operate CCTV cameras and other accessories. Units contain a power disconnect switch and LED indicators and have overload protection. The oversized enclosure is

hinged and vented, with convenient knockouts. Output provides camera synchronization and transient protection. Transformer has thermal protection. Cord set is included.

Part No.	Output Voltage	Amps	VA	No. of Outputs	Dimensions (W x H x D)	Weight	UL Listed
HPTV2401-E	24VAC	4	100	1	8.2" x 7.4" x 3.0"	6.7	No
HPV2801UL	28VAC	4	100	1	11.5" 10" x 4.9"	13.2	Yes
HPV2401UL	24VAC	4	100	1	11.5" x 10" x 4.9"	13	Yes
HPV2401ULZ	24VAC	4	100	1	11.5" x 10" x 4.9"	13	Yes
HPTV2404CB-E	24VAC	4	100	4	8.2" x 7.4" x 3.0"	10.8	No
HPTV2404-E	24VAC	4	100	4	8.2" x 7.4" x 3.0"	6.8	No
HPTV2404UL	24VAC	4	100	4	10" x 10" x 4.5"	8.3	Yes
HPV2404CB	24VAC	4	100	4	11.5" x 10" x 4.9"	10.8	No
HPV2404UL	24VAC	4	100	4	11.5" x 10" x 4.9"	10.8	Yes
HPTV2408CB-E	24VAC	4	100	8	8.2" x 7.4" x 3.0"	7.0	No
HPTV2408CE	24VAC	4	100	8	11.5" x 10" x 4.9"	10.9	No
HPTV2408-E	24VAC	4	100	8	8.2" x 7.4" x 3.0"	7.0	No
HPTV2408UL	24VAC	4	100	8	10" x 10" x 4.5"	8.4	Yes
HPV2408UL	24VAC	4	100	8	11.5" x 10" x 4.9"	10.9	Yes
HPV2408ULCB	24VAC	4	100	8	11.5" x 10" x 4.9"	10.9	Yes
HPTV2404-2	24VAC	8	200	4	11.5" x 10" x 4.9"	13.8	No
HPV2404-2UL	24VAC	8	200	4	11.5" x 10" x 4.9"	13.8	Yes



Part No.	Output Voltage	Amps	VA	No. of Outputs	Dimensions (W x H x D)	Weight	UL Listed
<b>HPV2404-2ULCB</b>	24VAC	8	200	4	11.5" x 10" x 4.9"	13.8	Yes
<b>HPV2408-1UL</b>	24VAC	8	200	8	11.5" x 10" x 4.9"	13.5	Yes
<b>HPV2408-1ULCB</b>	24VAC	8	200	8	11.5" x 10" x 4.9"	13.5	Yes
<b>HPTV2416CB-E</b>	24VAC	8	200	16	8.2" x 7.4" x 3.0"	14.3	No
<b>HPTV2416CE</b>	24VAC	8	200	16	11.5" x 10" x 4.9"	14.3	No
<b>HPTV2416-E</b>	24VAC	8	200	16	8.2" x 7.4" x 3.0"	10	No
<b>HPV2416UL</b>	24VAC	8	200	16	11.5" x 10" x 4.9"	14.3	Yes
<b>HPV2416ULCB</b>	24VAC	8	200	16	11.5" x 10" x 4.9"	14.3	Yes
<b>HPTV2408300</b>	24 or 28VAC	12 or 10	300	8	11.5" x 10" x 4.9"	14.3	No
<b>HPTV2408300CB</b>	24 or 28VAC	12 or 10	300	8	11.5" x 10" x 4.9"	18	No
<b>HPTV2416300</b>	24 or 28VAC	12 or 10	300	16	11.5" x 10" x 4.9"	18	No
<b>HPTV2416300CB</b>	24 or 28VAC	12 or 10	300	16	11.5" x 10" x 4.9"	18	No
<b>HPV2416-1UL</b>	24VAC	16	400	16	11.5" x 10" x 4.9"	17.5	Yes
<b>HPV2416-1ULCB</b>	24VAC	16	400	16	11.5" x 10" x 4.9"	17.5	Yes

# DC Video Power Distribution Units



Our DC CCTV power distribution units provide a constant source of power to operate CCTV cameras and other accessories. Units contain a power disconnect switch and LED indicators and have overload protection. The oversized enclosure is hinged and vented, with convenient knockouts. Output pro-

vides camera synchronization and transient protection. Transformer has thermal protection. Cord set is included.

Part No. Listed	Output Voltage	Amps	VA	No. of Outputs	Dimensions (W xH x D)	Weight	UL
HPV3DC4UL	6/12/24VDC	2.5	DC	4	11.5" x 10" x 4.9"	11.4	Yes
HPV3DC4ULCB	6/12/24VDC	2.5	DC	4	11.5" x 10" x 4.9"	11.4	Yes
HPV5DC8UL	6/12/24VDC	4.0 and 2.5	DC	8	11.5" x 10" x 4.9"	21.2	Yes
HPV5DC8ULCB	6/12/24VDC	4.0 and 2.5	DC	8	11.5" x 10" x 4.9"	21.2	Yes
HPTV5DC8CE	6/12/24VDC	4.0 and 2.5	DC	8	11.5" x 10" x 4.9"	21.2	No
HPV5DC16UL	6/12/24VDC	4.0 and 2.5	DC	16	11.5" x 10" x 4.9"	21.2	Yes
HPV5DC16ULCB	6/12/24VDC	4.0 and 2.5	DC	16	11.5" x 10" x 4.9"	21.2	Yes
HPTV5DC16CE	6/12/24VDC	4.0 and 2.5	DC	16	11.5" x 10" x 4.9"	21.2	No
HP1224ACDC	6/12/24VDC and 24VAC	4A DC and 4A AC	DC+100AC	16	14.5" x 15" x 2.75"	20	No

# Rack Mount Distribution Units



Contained in a 2U high 19" EIA rack enclosure, these power supplies have to save valuable installation space, a lighted power switch/circuit breaker and individual diagnostic LED's per output. CE models use 230VAC input. CB models have class 2 power limited output circuits.



HPR2432600CE

Part No.	Output Voltage	Amps	VA	No. of Outputs	Dimensions (W x H x D)	Weight (lbs)
HPR12DC416UL	12VDC	4	DC	16	19" x 3.25" x 9"	16.5
HPR12DC416CBUL	12VDC	4	DC	16	19" x 3.25" x 9"	16.5
HPR12DC616UL	12VDC	6	DC	16	19" x 3.25" x 9"	20.1
HPR12DC616CE	12VDC	6	DC	16	19" x 3.25" x 9"	20.1
HPR12DC616CBCE	12VDC	6	DC	16	19" x 3.25" x 9"	20.1
HPR12DC616CBUL	2VDC	6	DC	16	19" x 3.25" x 9"	20.1
HPR2416UL	24VAC	8	200	16	19" x 3.25" x 9"	19
HPR2416CBUL	24/28VAC	8	200	16	19" x 3.25" x 9"	19
HPR2416300UL	24/28VAC	12.5 or 10	300	16	19" x 3.25" x 9"	19.4
HPR2416300CBUL	24/28VAC	12.5 or 10	300	16	19" x 3.25" x 9"	19.4
HPR2432300UL	24/28VAC	12.5 or 10	300	32	19" x 3.25" x 9"	20.2
HPR2432300CBUL	24/28VAC	12.5 or 10	300	32	19" x 3.25" x 9"	20.2
HPR2416600UL	24/28VAC	25 or 20	600	16	19" x 3.25" x 9"	25.2
HPR2416600CE	24/28VAC	25 or 20	600	16	19" x 3.25" x 9"	25.2
HPR2416600CBUL	24/28VAC	25 or 20	600	16	19" x 3.25" x 9"	25.2
HPR2432600UL	24/28VAC	25 or 20	600	32	19" x 3.25" x 9"	25.2
HPR2432600CE	24/28VAC	25 or 20	600	32	19" x 3.25" x 9"	25.2
HPR2432600CBCE	24/28VAC	25 or 20	600	32	19" x 3.25" x 9"	25.2
HPR2432600CBUL	24/28VAC	25 or 20	600	32	19" x 3.25" x 9"	25.2

# Weatherproof NEMA 4X Power Supplies



Contained in a non-metallic NEMA 4X/IP66 rated enclosure, these power supplies are rated for the outdoors! The door is hinged and fully gasketed, with a lockable HASP. Mounts to flat surfaces with included corrosion-free hardware, or to poles with the optional pole mount kit.



HPBX

Part No.	Output Voltage	Amps	VA	No. of Outputs	Dimensiona (W x H x D)	Weight
HPS5WP	6/12/24VDC	2	DC	1	10" x 12" x 6"	13.4
HPTV5DC04WP	6/12/24VDC	2	DC	4	10" x 12" x 6"	13.6
HP24100WP	24VAC	4	100	1	10" x 12" x 6"	10.6
HP24100WPJ	24VAC	4	100	1	6" x 6" x 4"	8
HP24100WPCE	24VAC	4	100	1	10" x 12" x 6"	10.6
HPBWPX	Enclosure and mounting plate only				10" x 12" x 6"	5
HPBWPJ	Enclosure and mounting plate only				6" x 6" x 4"	2.5
HPTV2404WP	24VAC	4	100	4	10" x 12" x 6"	13
HPTV2408WP	24VAC	4	100	8	10" x 12" x 6"	13.5
HPTV2401WPS	24VAC	8	200	1	10" x 12" x 6"	13.1
HPTV2401WPZ	24VAC	8	200	1	10" x 12" x 6"	13.1
HP24200WP	24VAC	8	200	1	10" x 12" x 6"	12
HPTV2404WP-2	24VAC	8	200	4	10" x 12" x 6"	13.1
HP28100WP	28VAC	3.6	100	1	10" x 12" x 6"	10.6
HPTV2804WP	28VAC	3.6	100	4	10" x 12" x 6"	10.6
HPTV2808WP	28VAC	3.6	100	8	10" x 12" x 6"	13
HPTV2801WPS	28VAC	6.25	175	1	10" x 12" x 6"	13.4
HPTV2801WPZ	28VAC	6.25	175	1	10" x 12" x 6"	13.4
HP28175WP	28VAC	6.25	175	1	10" x 12" x 6"	13
HPTV2804WP-2	28VAC	6.25	175	4	10" x 12" x 6"	13.1

# Access Control Power Supplies



The access control power supplies/chargers will convert 115VAC / 60Hz into field-selectable continuous power output. Many of these power supplies are UL listed for access control (UL294), fire alarm (UL1481) and burglar alarm installations (UL603), and conform to NEC requirements.



**HP600ULACM8**

Part No.	Output Voltage	Amps	No. of Outputs	Dimensions (W x H x D)	Weight (Lbs.)	UL Listed
<b>HP312CX</b>	6/12/24VDC	2.5 or 1	1	11.5" x 10" x 4.9"	12.8	Yes
<b>HP512CX</b>	6/12/24VDC	4 or 2.5	1	11.5" x 10" x 4.9"	14.6	Yes
<b>HP300ULX</b>	12/24VDC	2.5	1	13.5" x 17" x 4.25"	14.7	Yes
<b>HP300ULPD4CB</b>	12/24VDC	2.5	4	13.5" x 17" x 4.25"	14.7	Yes
<b>HP300ULM</b>	12/24VDC	2.5	6	13.5" x 17" x 4.25"	14.9	Yes
<b>HP400ULPD4CB</b>	12/24VDC	4	4	13.5" x 17" x 4.25"	17.1	Yes
<b>HP400ULPD8CB</b>	12/24VDC	4	8	13.5" x 17" x 4.25"	16.9	Yes
<b>HP400ULX</b>	12/24VDC	4	1	13.5" x 17" x 4.25"	16.8	Yes
<b>HP400ULACM4</b>	12/24VDC	4	4	13.5" x 17" x 4.25"	17.5	Yes
<b>HP400ULM</b>	12/24VDC	4	6	13.5" x 17" x 4.25"	17.5	Yes
<b>HP600ULACM8</b>	12/24VDC	6	8	13.5" x 17" x 4.25"	18.9	Yes
<b>HP600ULX</b>	12/24VDC	6	1	13.5" x 17" x 4.25"	18.3	Yes
<b>HP600ULM</b>	12/24VDC	6	6	13.5" x 17" x 4.25"	18.2	Yes
<b>HP600ULPD8CB</b>	12/24VDC	6	8	13.5" x 17" x 4.25"	18.5	Yes
<b>HP600ULPD16CB</b>	12/24VDC	6	16	13.5" x 17" x 4.25"	18.7	Yes

# Fire Alarm Power Supplies




Fire Alarm power supplies are capable of connecting to most brands of UL listed fire alarm control panels to offer notification appliance circuit expansion. Features include 6, 8, 9 or 12 amp 24 VDC operation, supervised inputs, and 4 NAC outputs with strobe synchronization protocols built in for notification appliances.



HPF24S6E

Part No.	Cabinet	Amps	Dimensions	Weight (lbs.)	Fire Market	Listings
HPF602ULADA	Black	6	12.25" x 16.0" x 3.0"	9.1	US	UL, CSFM, MEA
HPF24S6	Red	6	14.5" x 15" x 2.75"	21.2	US	UL, CSFM, MEA, FM
HPF24S6E	Red	6	14.5" x 15" x 2.75"	21.2	Export	UL, CSFM, MEA, FM
HPF24S6C	Red	6	14.5" x 15" x 2.75"	21.2	Canada	ULC
HPF24S8	Red	8	14.5" x 15" x 2.75"	21.2	US	UL, CSFM, MEA, FM
HPF24S8E	Red	8	14.5" x 15" x 2.75"	21.2	Export	UL, CSFM, MEA, FM
HPF24S8C	Red	8	14.5" x 15" x 2.75"	21.2	Canada	ULC
HPF902ULADA	Black	9	12.25" x 16.0" x 3.0"	9.6	US	UL, CSFM, MEA
HPFF8	Red	8	16.65" x 19 x 5.2"	21	US	UL, CSFM, FDNY
HPFF12	Red	12	16.65" x 19 x 5.2"	24	US	UL, CSFM, FDNY
HPFF8CM	Chassis	8	24" x 46 x 5.2"	12	US	UL, CSFM, FDNY
HPFF12CM	Chassis	12	24" x 46 x 5.2"	15	US	UL, CSFM, FDNY


# Power Distribution Models



These power distribution modules provide a convenient way to protect your control and load circuits from over-current conditions. Models have glass or automotive style one-use fuses, or PTC auto-reset type devices. They make an excellent power distri-

bution solution from a centralized power source and some have added features like fire alarm interface or access control functionality.


Part No.	Output Voltage	Amps	VA	No. of Outputs	Dimensions (W x H x D)	Weight (Lbs.)	UL Listed
<b>HPACM4</b>	12/24VDC	N/A	DC	4	4.5" x 8" x 1.25"	0.8	Yes
<b>HPMOM6</b>	12/24VDC	N/A	DC	5	3.5" x 5.3" x 1"	0.8	Yes
<b>HPACM8</b>	12/24VDC	N/A	DC	8	4.5" x 8" x 1.25"	1.1	Yes
<b>HPTV09</b>	12/24VDC	N/A	DC	9	4.3" x 6.5" x 2.0"	0.6	Yes
<b>HPD4</b>	28VAC/VDC	N/A	DC	4	4.3" x 3.0" x 1.0"	0.3	No
<b>HPD4CB</b>	28VAC/VDC	N/A	DC	4	4.3" x 3.0" x 1.0"	0.3	No
<b>HPD8</b>	28VAC/VDC	N/A	DC	8	4.3" x 3.0" x 1.0"	0.3	No
<b>HPD8CB</b>	28VAC/VDC	N/A	DC	8	4.3" x 3.0" x 1.0"	0.3	No



**HPACM8**



**HPTV09**



**HPMOM6**

# Transformers

Transformers are used stand-alone in CCTV, access and security systems, as well as in combination with general purpose power supplies. Honeywell offers AC and DC versions of the plug in units as well as AC open frame versions.



## AC Plug-in Transformers

The HTP Series plug-in AC transformers come in several sizes. They have a case mounting tab to keep them secured to the wall outlet, and screw terminals for power lead wires. This series of transformers have built-in thermal protection and are UL-Recognized, Class 2.

## AC Open Frame Transformers

The HT Series open frame AC transformers come in several sizes. They provide color-coded lead wires for connections and have screw down mounting feet. This series of transformers has built-in thermal protection and are UL-Recognized. Typically they are mounted in enclosures.


## DC Plug in Switching Transformers

The HPT Series plug-in 12VDC power supplies come in several sizes. These power supplies are fully regulated and filtered, with output rated 12VDC. They are switching supplies that are higher efficiency than linear designs. The output is a 2.1 mm coax plug which is center positive. UL Listed/ CSA Approved.

HTP1220	12VAC/20VA PLUG IN XFMR w/FUSE
HTP1620	16VAC/20VA PLUG IN XFMR w/FUSE
HTP1640	16VAC/40VA PLUG IN XFMR w/FUSE
HPT1850	18VAC/50VA PLUG IN XFMR w/FUSE
HTP2420	24VAC/20VA PLUG IN XFMR w/FUSE
HTP2440	24VAC/40VA PLUG IN XFMR w/FUSE
HTP245	24VAC/50VA PLUG IN XFMR w/FUSE
HT28100	28VAC/100VA WIRE IN XFMR w/FUSE
HT28175	28VAC/175VA WIRE IN XFMR w/FUSE
HT24100	28VAC/100VA WIRE IN XFMR w/FUSE
HT24200	28VAC/200VA WIRE IN XFMR w/FUSE
HTP12DC3000	12VAC/3AREG PLUG IN w/COAX PLUG
HTP12DC1500	12VAC/1.5AREG PLUG IN w/COAX PLUG
HTP12DC1000	12VAC/1AREG PLUG IN w/COAX PLUG
HTP12DC500	12VAC/.5AREG PLUG IN w/COAX PLUG
HTP12DC300	12VAC/.3AREG PLUG IN w/COAX PLUG
HP2412IL8	24VAC TO 12VDC/800mA CONVERTER

# Relays and Timers

Honeywell has convenient accessories and control relays that help installers speed through jobs and customize installations to meet end-user demands. Typical uses are in CCTV, security, and access control systems which require that little extra to make the system run just right.



HPT724



HRB610



HRB5

## HRB5 Relay Unit

For dry or latching contact, polarity reversal, phone line seizure or other switched control. 6VDC or 12VDC jumper selectable operation. Coil draws 120mA. A/120VAC/28VDC DPDT contacts

## HRB1224 Relay Unit

For dry or latching contact, polarity reversal, phone line seizure or other switched control. 12VDC or 24VDC jumper selectable operation. Coil draws 120mA. A/120VAC/28VDC DPDT contacts.

## HRB610 Multi-voltage Control Relay

Control relay cluster offers SPDT contacts which may be operated by 12 VDC or 12 VAC by wiring to the input terminals or 24 VDC or 24 VAC by cutting a resistor. 50 mA coil draw per module position. Coil input is diode polarized to allow reverse polarity control. One red LED per module position. Load is rated resistive, 10A @ 120 VAC/28 VDC or 7A @ 230 VAC.

## HPT724 Programmable LCD Timer

Programmable LCD event timer is equipped with an independent-

ly controlled form "C" relay that provides 50 latching and/or momentary operations per week during a programmed schedule of your choice. Programming 24 hour 365 day events done prior to, or during field installation and battery protects against loss of programming.

## HPT6062 Programmable Multi-Purpose Timer

Programmable multi-purpose timer suitable for applications that require a timed delay operation. Accurate time adjustment range (programmable from 1 second to 60 minutes). 12VDC or 24VDC operation. LED indicates relay is energized. Form "C" relay contacts are rated for 8A @ 120VAC/ 28VDC.

## HRBSN Sensitive Relay Unit

The HRBSN is a high sensitivity relay module that is used for dry or latching contacts, polarity reversal, phone line seizure, or other switched controls. The high sensitivity coil on this module allows the relay to operate while drawing substantially less current than most standard relay packages.

# Accessories

No job would be complete without the power accessories that make installation convenient, neat and easy.



Accessory Family



HP1A/20MM



HPT Cover

## HST34 Snap Track Mount

Snap track provides a secure mounting surface for the card type power supplies and relay units. Generally used when a more solid installation is needed, it is made from gray plastic. Convenient 4-inch length comes three pieces to a box.

## HPB407 Electrical Enclosure

This enclosure is made from 16 gauge steel construction with black pebble grained powder coat finish and is used to contain batteries, power supplies and transformers. For convenient operation, it has a hinged cover and vented enclosure with five convenient knockouts. Dimensions: 11.5" W x 5" D x 10" H

## HPCORDCE

6ft 3 Conductor 230V CE Power Cord with IEC320 C13 connector and Shuko plug

## HPCORDUS

6ft 3 Conductor 120V US Power Cord with NEMA 5 plug and stripped end

## HPCORDUS12

12ft 3 Conductor 120V US Power Cord with NEMA 5 plug and stripped end

## HP1A/20MM-10

1A Glass Fuse, 5x20mm, Qty=10

## HP2A/20MM-10

2A Glass Fuse, 5X20mm, Qty=10



Snaptrack



HPTV-PMK4



HP10A/SAUTO-10

#### **HP3A/20MM-10**

3A Glass Fuse, 5X20mm, Qty=10

#### **HP6A/20MM-10**

6A Glass Fuse, 5X20mm, Qty=10

#### **HP3A/SAUTO-10**

3A Standard Auto Fuse VIOLET, Qty=10

#### **HP5A/SAUTO-10**

5A Standard Auto Fuse TAN, Qty=10

#### **HP10A/SAUTO-10**

10A Standard Auto Fuse RED, Qty=10

#### **HPTV-PMK2 / HPTV-PMK3 / HPTV-PMK4 Pole Mount Kits**

Stainless steel pole mount kits designed to securely mount Honeywell Weatherproof NEMA 4X enclosures to a vertical or horizontal pole in an outdoor installation. The PMK Series will mount to 2", 3" and 4" poles depending on model selected.

#### **HPTCOVER**

Plug-in transformer enclosure protects AC plug-in transformers and ensures that it remains securely fixed to the AC wall outlet. It's made from 16 gauge steel construction with black pebble grained powder coat finish, and has a removable cover. Enclosure has convenient knockouts.



## Find out more

[www.honeywellpower.com](http://www.honeywellpower.com)

## Honeywell Fire Systems

Honeywell Power Products

12 Clintonville Road

Northford, CT 06472

Tel: 203.484.7161

Fax: 203.484.7118

[www.honeywell.com](http://www.honeywell.com)

M-PG-HPP

February 2010

Printed in U.S.A.

© 2010 Honeywell International Inc.

**Honeywell**